

13 POINT CONTROLLER FULLY PROGRAMMABLE

OVERVIEW

The HVAC controls market requires a DDC controller that provides consolidated control with mid-range capability in a fully programmable, feature-rich LonMark® certified device.

The Circon™ UHC-320 unites a variety of configurable control blocks combined with the power of the Circon BASIC programming language to provide exceptional application flexibility. The UHC-320 is all you need in a 13-point DDC controller.

APPLICATIONS

Use the UHC-320 to implement tailored control applications for unique or custom HVAC mechanical designs. The UHC-320's 6 universal inputs and 7 universal outputs, and all control blocks are easily configured using simple Windows®-based software. Flexible alarm, trend, schedule and PID control blocks can be used to quickly create effective control and monitoring solutions.

Circon's powerful BASIC programming language can be used, along with the configurable control blocks and the input/output points to implement more complicated control sequences. Circon BASIC is flexible and powerful, allowing a user with limited programming experience to create tailored control sequences for packaged units such as fan coil units, air handlers, rooftop units with economizer, and terminal units such as heat pumps and unit ventilators or any custom HVAC mechanical design.

The Windows®-based configuration and viewer software provided with the UHC-320, complemented by the Circon BASIC Compiler, is all fully compatible with Echelon® Corporation's LNS® software.

ORDERING INFORMATION

Part number 10-0376



FEATURES AND BENEFITS

- Seamless integration into interoperable LonWorks® networks
- Fully programmable with easy to use Circon BASIC programming language
- Six universal inputs configurable for voltage, current, resistance and dry contacts
- Seven universal outputs configurable for voltage, current, and digital
- Onboard real-time clock allows for time-based events, data logging, and network master operation
- All memory is protected with a lithium battery
- Quick network access through an audio jack
- Faster, easier to use LNS plug-ins
- Adaptable for stand-alone or networked operation
- LonMark certified



LONMARK^{3.3}



LONMARK[®]
PARTNER



SPECIFICATIONS

I/O CAPABILITY

6 Universal inputs	10 k Ω thermistor, 1 k Ω RTD, 4–20 mA current, 0–10 VDC, digital (dry contact)
7 Universal outputs	4–20 mA current, 0–10 VDC, digital. Maximum drive 100 mA per output

COMMUNICATIONS

Transceiver	Echelon Free Topology Transceiver (FTT-10A) @ 78 kbps
Wire type	AWG22 to AWG16 stranded (use only twisted pair wiring and copper conductors for network)
Neuron [®]	3150, 10 MHz

POWER SUPPLY

Controller	1.6 A, 24 VAC 50–60 Hz or 24 VDC
Fuse	2.5 A slow-blow (Bussman GMD-2.5A, Littelfuse 23902.5A)
Power fail protection	Lithium battery retains data in RAM and clock

MECHANICAL

Operating temperature	32°F to 122°F (0°C to 50°C)
Relative humidity	5% to 95% RH (non-condensing)
Weight	1 lb. 1 oz. (485 grams)
Dimensions:	1.9" x 5" x 9" (48 mm x 127 mm x 229 mm)
Enclosure material:	PVC, inflammability class V0 (UL94) and metal
Mounting	DIN rail

AGENCY LISTINGS AND REGULATORY COMPLIANCE

Class II device (when powered by class II supply)
 CSA 22.2 #205-M1983, #950-M89
 UL 916 certification for Energy Management Equipment
 Part 15, Part J, Class A of the FCC rules for Radio Frequency Devices
 EMC Directive 89/336/EEC
 LonMark 3.3 certified

CIRCON SYSTEMS CORPORATION

110 – 6660 McMillan Way, Richmond, BC, Canada V6W 1J7
 telephone 604.232.4700 technical support 1.877.350.2299 facsimile 604.232.4747
 toll free 1.800.338.1866 website www.circon.com



Specifications subject to change without notice.

Circon™ is a trademark of Circon Systems Corporation. Echelon®, LonWorks®, Neuron®, and LNS® are trademarks of the Echelon Corporation registered in the United States and other countries. Windows® is a trademark of Microsoft Corporation registered in the United States and other countries. LonMark® and the LonMark Logo are managed, granted and used by LonMark International under a license granted by Echelon Corporation.

PART # 80-0258 / REVISION # 1.8 / PRINTED IN CANADA